

US008143660B2

(12) United States Patent

Lee et al.

(10) Patent No.:

US 8,143,660 B2

(45) Date of Patent:

Mar. 27, 2012

(54)	METHOD FOR MANUFACTURING OXIDE
	FILM HAVING HIGH DIELECTRIC
	CONSTANT, CAPACITOR HAVING
	DIELECTRIC FILM FORMED USING THE
	METHOD, AND METHOD FOR
	MANUFACTURING THE SAME

(75) Inventors: Jung-hyun Lee, Gyeonggi-do (KR); Burn-seok Seo, Seoul (KR); Yo-sep

Cho, Gyeonggi-do (KR)

Min, Gyeonggi-do (KR); Young-jin

(73) Assignee: Samsung Electronics Co., Ltd.,

Gyeonggi-do (KR)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 215 days.

(21) Appl. No.: 10/797,046

(22) Filed: Mar. 11, 2004

(65) Prior Publication Data

US 2004/0238872 A1 Dec. 2, 2004

(30) Foreign Application Priority Data

Mar. 11, 2003 (KR) 10-2003-0015197

(51) Int. Cl. *H01L 27/108*

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

3,996,021 A	*	12/1976	Chang et al	428/564
6.020,024 A	١.	2/2000	Maiti et al.	
6.486,080 E	32 *	11/2002	Chooi et al	438/785
6,844,604 E	32 *	1/2005	Lee et al	257/410

6,930,059 6,936,881 7,112,539	B2 *	8/2005	Conley et al Yeo et al Lee et al.	257/310
2002/0014647	Al*	2/2002	Seidl et al.	

FOREIGN PATENT DOCUMENTS

KR	10-2001-00228836 A	4/2001
KR	10-2002-0002991 A	1/2002
KR	1020020032054	5/2002
KR	1020030002298	1/2003

OTHER PUBLICATIONS

Korean Office Action dated Jan. 11, 2010, in corresponding Korean Application No. 10-2003-0015197, with English translation. Sneh, Oler et al., Thin film atomic layer deposition equipment for semiconductor processing, Thin Solid Films 402 (2002) 248-261.

Office Action issued by Chinese Patent Office on Mar. 21, 2007 for Cinese Patent Application No. 2004100283929.

English Translation of Office Action by Chinese Patent Office on Mar. 21, 2007 for Chinese Patent Application No. 2004100283929. English translation of Korean Office Action dated Nov. 8, 2011 in corresponding Korean Application No. 10-2003-0015197.

* cited by examiner

Primary Examiner — Ori Nadav (74) Attorney, Agent, or Firm — Harness, Dickey & Pierce,

(57) ABSTRACT

Provided are a method for manufacturing a high k-dielectric oxide film, a capacitor having a dielectric film formed using the method, and a method for manufacturing the capacitor. A high k-dielectric oxide film is manufactured by (a) loading a semiconductor substrate in an ALD apparatus, (b) depositing a reaction material having a predetermined composition rate of a first element and a second element on the semiconductor substrate, and (c) forming a first high k-dielectric oxide film having the two elements on the semiconductor substrate by oxidizing the reaction material such that the first element and the second element are simultaneously oxidized. In this method, the size of an apparatus is reduced, productivity is enhanced, and manufacturing costs are lowered. Further, the high k-dielectric oxide film exhibits high dielectric constant and low leakage current and trap density. Thus, a capacitor including the high k-dielectric oxide film as a dielectric film also exhibits low leakage current and trap density.

1 Claim, 10 Drawing Sheets

